



PLUG & SEAL CONNECTORS

Plug & Seals are rubber-coated pipe sections that create a safe, leak-free connection between housings. A secure, low-cost solution for the transport of air, water, and oils, they can combine several functions in a single component and compensate for conduit misalignment and tolerance variations. Plug & Seals are available in a wide variety of elastomer coatings.

Plug & Seals are useful in a wide range of applications including:

- Water and oil circuits
- Air routing systems of internal combustion engines
- Ancillary engine components such as superchargers, turbochargers or intake manifolds
- Automatic and manual transmission systems
- Valve and pipework systems
- Heating and air-conditioning systems



VALUES TO THE CUSTOMER

Plug & Seal plug connections from Freudenberg Sealing Technologies provide many technical and cost benefits:

- Create a reliable seal even in high-pressure applications
- Give simple, secure, and low-cost fitting
- Ensure acoustic and mechanical decoupling
- Minimize maintenance costs due to greatly improved service life
- Compensate for misalignment and permit greater tolerances on installation
- Reduce logistics costs
- Combine several functions in a single component
- Offer clear benefits through lower total cost
- Design development according to customer-specific requirements

PLUG & SEAL CONNECTORS



FEATURES AND BENEFITS

FLEXIBLE COMPONENTS

Selection of materials

Rubber coatings and shock absorption are available with modern elastomer materials—for a range of different physical requirements. Customers are also free to choose the base material of the pipe section: steel, aluminium or plastic. Thanks to the flexible range of materials the plug connections can be used in virtually all sectors of fluids and gas transport.

Plug & Seal Connectors are designed according to customer specifications and are also available in standard dimensions for quick sampling.

Elastomer coating

- FKM
- ACM
- VMQ
- EPDM
- HNBR
- AEM
- NBR

Base part

- Steel
- Aluminum
- Plastic

Sealing Beads

Shock absorber



Dimensions available for quick sampling in bold:

External diameter* [mm] Plug & Seal (A)**	Locating bore [mm] (acc. to H8) (B)***	Internal diameter pipe [mm] (R1)	Plug & Seal Length [mm] (L)					
15.5	15	10	20	25	30	40	50	60
20.7	20	14	20	25	30	40	50	60
25.9	25	18	20	25	30	40	50	60
30.9	30	22	20	25	30	40	50	60
40.9	40	32	20	25	30	40	50	60

Wall thickness of base part (b):

1.0 mm (Plug & Seal for locating bore 15, 20, 25 mm)

1.5 mm (Plug & Seal for locating bore 30, 40 mm)

*Not all dimensions available

**Minimum compression of 15%

***Recommended values, depending on elastomer base material: steel (bonderised)

The information contained herein is believed to be reliable, but no representation, guarantees or warranties of any kind are made to its accuracy or suitability for any purpose. The information presented herein is based on laboratory testing and does not necessarily indicate end product performance. Full scale testing and end product performance are the responsibility of the user.